IN THE CLAIMS

This listing of claims replaces all prior listings.

1. (Currently Amended) An anode material, comprising:

a composite material including a base material physically bonded by van der Waals forces to a carbonaceous material,

wherein,

_____the base material including includes tin (Sn) and at least one element selected from the group including cobalt (Co) and iron (Fe) Group 14 elements, except for carbon (C),

a mass ratio of the carbonaceous material in the composite material is within a range of 0.1 to 8.0 inclusive relative to 100 for the base material, and

the physical bonding of the base material to the carbonaceous material effected by applying a compressive force and a shearing force to at least a part of a surface of a base material when the composite material is formed.

- 2. (Currently Amended) An anode material according to claim 1, wherein the base material further includes at least one kind selected from the group consisting of scandium (Sc), titanium (Ti), vanadium (V), chromium (Cr), manganese (Mn), iron (Fe), cobalt (Co), nickel (Ni), copper (Cu), zinc (Zn), boron (B), aluminum (Al), gallium (Ga), indium (In) and silver (Ag).
- 3. (Original) An anode material according to claim 1, wherein the carbonaceous material is acetylene black.
- 4. (Original) An anode material according to claim 1, wherein the carbonaceous material is artificial graphite.
- 5. (Original) An anode material according to claim 1, wherein the carbonaceous material is carbon fiber.
 - 6. (Cancelled)

7. (Currently Amended) A battery, comprising:

a cathode;

an anode; and

an electrolyte,

wherein,

the anode comprises a composite material including a base material physically bonded by van der Waals forces to a carbonaceous material,

the base material including <u>tin (Sn) and at least one element selected from the group including cobalt (Co) and iron (Fe) Group 14 elements, except for carbon (C), and iron (Fe) Group 14 elements, except for carbon (C),</u>

a mass ratio of the carbonaceous material in the composite material is within a range of 0.1 to 8.0 inclusive relative to 100 for the base material, and

the physical bonding of the base material to the carbonaceous material effected by applying a compressive force and a shearing force to at least a part of a surface of a base material when the composite material is formed.

- 8. (Currently Amended) A battery according to claim 7, wherein the base material further includes at least one kind selected from the group consisting of scandium (Sc), titanium (Ti), vanadium (V), chromium (Cr), manganese (Mn), iron (Fe), cobalt (Co), nickel (Ni), copper (Cu), zinc (Zn), boron (B), aluminum (Al), gallium (Ga), indium (In) and silver (Ag).
- 9. (Original) A battery according to claim 7, wherein the carbonaceous material is acetylene black.
- 10. (Original) A battery according to claim 7, wherein the carbonaceous material is artificial graphite.
- 11. (Original) A battery according to claim 7, wherein the carbonaceous material is carbon fiber.
 - 12. (Cancelled)